



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19

AP8653

Call for More Information 0800 2799254

- APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
- Includes: CAN port terminator, Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable

Output	
Nominal Output Voltage	230V
Overload Protection	Yes
Maximum Total Current Draw	32
Output Connections	(3) IEC 60320 C19 (21) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 2P + E
Cord Length	3meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	7400VA
Maximum Input Current	32A
Maximum Line Current	32A

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Maximum Height	1829MM, 182.9CM
Maximum Width	56MM, 5.6CM
Maximum Depth	51MM, 5.1CM
Net Weight	8.23KG
Shipping weight	10.5KG
Shipping Height	2038MM, 203.8CM
Shipping Width	162MM, 16.2CM
Shipping Depth	118MM, 11.8CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Elevation	0 - 15240meters

Conformance	
Approvals	EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.